CV9035 MkIII







Specifications

General	
Weight, combat loaded	32 000 – 35 000 kg
Personnel	10 men
Length	6.8 m
Width	3.2 m
Height	2.8 m
Ground clearance	0.4 m
Performance	
Speed	
forward	70 km/h
reverse	40 km/h
Slope	60%
Side slope	40%
Trench crossing	2.6 m
Vertical wall climbing	1.0 m
Fording	1.5 m
Typical cruising range	600 km
Survivability	
Hull and turret structure	armour steel
Add-on-Armour	yes
Defensive Aid Suite	yes
NBC protection	yes
Air-condition system	yes
Fire extinguishing system	yes
Communications	
Radio	yes
Intercommunication	yes

Turret	
Main armament	35/50 mm
Bushma	ster III, 35/50 cannon,
	dual feed
Rate of fire single, low	rate and high rate burst
Calibre and ammunition	35 mm x 228 mm
	fires all NATO qualified
	35 mm ammunition
ready rounds	2 x 35 rds
stowed rounds	typical 140 rds
Traverse range	n x 360deg
Elevation range	-8 to +37 deg
Secondary armament	7.62 mm
elevation	-10 to +50 deg
Close defence	dischargers
Fire control system	
Gun turret drive system	electrical, direct
Fire Control Computer	digital processor
Stabilisation system	dual axis stabilised
	top mirror, slaved gun
ir	dependent line of sight
Gunner's sight	full FCS
day channel	X8, X1 periscopic
thermal night channe	l yes
laser range finder	yes
Commander's sight	full FCS
hunter killer capabilit	y yes
day channel	X6, X1
thermal night channe	l yes

Barrel camera

Engine	
Туре	diesel, 4 cycle stroke
Power	up to $600 \text{kW} / 2350 \text{rpm}$
Transmission	
Gearranges	4 forward, 2 reverse,
electronically controlled, fully automatic	
Running gear	
Suspension type	torsion bars with
	rotary dampers
Track width	0.5 m
Ground contact	4.1 m
Track tensioning system	n semi-active hydraulic
Electrical system	
Voltage (DC)	24 V
Batteries	500 Ah
Multiplex system	CAN bus

Vehicle control and information system

High Speed Data Bus

Built in test
On-line manuals
Embedded training
Video network
Defensive aid suite integration



Ethernet

FOR MORE INFORMATION CONTACT:

BAE Systems Hägglunds AB SE-891 82 Örnsköldsvik Sweden Telephone +46 (0)660 800 00 Fax +46 (0)660 151 90 www.baesystems.com/hagglunds This document gives only a general description of the product(s) or services and except where expressly provided otherwise shall not form part of any contract. From time to time, changes may be made in the products or the conditions of supply.